

MATERIAL SAFETY DATA SHEET

ADDRESS: Heat and Light Resources d/b/a HeatCell PO Box 1033 Jane Lew, WV 26378 (304) 326-2624		DATE: 01/02/00	NFPA HAZARD CLASSIFICATIONS H = HEALTH F = FLAMMABILITY R = REACTIVITY NF = NOT FOUND H = 1 F = 1 R = 1
		PREPARED BY: Dr. Charles Simon	
		EMERGENCY TELEPHONE NUMBER: CHEMTREC 800-424-9300	
I. IDENTIFICATION			
LABEL NAME:		FOOD WARMER	
TRADE OR PRODUCT NAME:		EcoFuel™ XB/HeatCell	
FDA NO.:	CAS NO.:	Diethylene Glycol CAS 00111-46-6	

II. FIRE, EXPLOSION AND REACTIVITY DATA

FLASH POINT (METHOD):	246°F (104°C) Cleveland Open Cup	0 = LEAST 1 = SLIGHT 2 = MODERATE 3 = HIGH 4 = EXTREME
EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM OR CO ₂	DOT HAZARD CLASSIFICATION: NOT REQUIRED	
SPECIAL FIRE FIGHTING PROCEDURES: UNUSUAL FIRE AND EXPLOSION HAZARDS:	NONE UNKNOWN, Believed to be relatively safe.	
HAZARDOUS COMBUSTIBLE OR DECOMPOSITION PRODUCTS: Product consists of hydrocarbon component stabilized by tightly packed fiber wool to give an essentially non-spillable mass. The components are contained in a metal can with a metal lid. The mass is not ignitable at room temperature. To ignite, apply flame directly to glass fiber(s). Can produce carbon monoxide and some irritants under some burning conditions. Glass fibers caused cancer in animals through unnatural routes of exposure (surgical implantation), but it is not associated with cancer by inhalation. Use of glass fibers has not been shown to cause cancer in humans. If ingestion of glass fibers occur, observe individual for several days to ensure that intestinal blockage does not occur. It is not recommended to induce vomiting if ingested.		
STABILITY: Stable CONDITIONS TO AVOID: Excessive Heat. MATERIALS TO AVOID: Strong Oxidizers.		
HAZARDOUS POLYMERIZATION PRODUCTS: NA Will not occur.		

III. PHYSICAL DATA

ODOR, APPEARANCE AND PHYSICAL STATE: Slightly opaque colorless liquid with subtle petroleum solvent odor.		
BOILING POINT:	433°F 223°C	SPECIFIC GRAVITY (H ₂ O = 1.0): 1.117 @ 68°F (20°C)
MELTING POINT:	NA	EVAPORATION RATE: < 1 (Butyl Acetate = 1)
VAPOR PRESSURE:(mm/Hg) < 1 @20°C, DEG = 0.01	SOLUBILITY IN WATER: Partially Miscible	
VAPOR DENSITY (AIR = 1): > 1		

IV. PROTECTION INFORMATION

RESPIRATORY: Use MSHA or NIOXH respirator for handling vapor or mist.	VENTILATION: Always use with Good ventilation.
EYE: Safety glasses for working with vapors or mists.	SKIN: Protective gloves or clothing generally not needed.
OTHER PROTECTIVE DEVICES AND PROCEDURES: Generally not required. Avoid prolonged breathing of mist. Wash hands after handling. Wash soiled work clothing frequently.	

V. OCCUPATIONAL EXPOSURE LIMIT

THRESHOLD LIMIT VALUE (TLV): NF
OSHA PERMISSIBLE EXPOSURE LIMIT (PEL): NF
HAS THE SUBSTANCE BEEN LISTED AS A CARCINOGEN OR POTENTIAL CARCINOGEN IN THE ANNUAL REPORT ON CARCINOGENS, PUBLISHED BY NTP, BY THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER, OR BY OSHA? YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>

VI. HEALTH HAZARD INFORMATION

HEALTH HAZARD DETERMINATION:

INHALATION: *Acute:* Irritation, especially with mists. *Chronic:* Irritation.

SKIN CONTACT: *Acute:* Defatting, irritation and mild discomfort. *Chronic:* Same as Acute.

INGESTION: *Acute:* May cause headache, nausea, dizziness. *Chronic:* Renal damage.

SIGNS AND SYMPTOMS OF EXPOSURE.

Possible drowsiness, behavior changes, vomiting, diarrhea due to DEG poisoning. For advanced stages, renal damage or failure.

MEDICAL SYMPTOMS GENERALLY AGGRAVATED BY EXPOSURE:

Nervous system damage, renal weakness and dermatitis.

VII. EMERGENCY AND FIRST AID PROCEDURES

INHALATION EXPOSURE: Remove to fresh air, get medical attention if symptoms persist.

EYE CONTACT: Flush with water, get medical attention if symptoms persist.

SKIN CONTACT: Wash with soap and water, get medical attention if needed.

INGESTION: Drink 2 glasses of water and induce vomiting immediately, get medical attention. If convulsing or unconscious, do not induce vomiting or give medication.

VIII. SPILL, LEAK AND DISPOSAL PROCEDURES

PRECAUTIONS IF MATERIAL IS SPILLED OR RELEASED:

Contain spills with absorbent material (clay, soil, etc.)
Shovel up. Avoid skin and eye contact. Dispose of in accordance with local, state and federal regulations.

WASTE DISPOSAL METHODS:

In accordance with local, state and federal regulations for glycols. Package should be opened and contents soaked up with absorbent materials.

IX. HANDLING AND STORAGE PROCEDURES

Avoid skin and eye contact. Avoid breathing mists. Do not overheat. Do not mix with other fuels or oxidizing agents. Use proper breathing apparatus for extended handling of mist or liquid.

X. CHEMICAL AND COMMON NAMES

Diethylene glycol

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM CURRENT AND REPUTABLE SOURCES. HOWEVER, THE DATA IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS OR ACCURACY. IT IS THE USER'S RESPONSIBILITY BOTH TO DETERMINE SAFE CONDITIONS FOR USE OF THIS PRODUCT AND TO ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE OR EXPENSE RESULTING FROM IMPROPER USE OF THIS PRODUCT.